

SDS: DAVCO PANEL SKIMCOAT (INTERNAL)

SAFETY DATA SHEET

1. IDENTIFICATION

PRODUCT NAME	DAVCO PANEL SKIMCOAT (INTERNAL)
CHEMICAL FAMILY	Cement / sand mixture
EMERGENCY CONTACT	ParexGroup Pte Ltd 28 Tuas South Avenue 8 Singapore 637648 Telephone : +65-68610632

2. HEALTH HAZARD IDENTIFICATION

ACUTE	Cement and sand are "Nuisance dusts" that are irritants to eyes, skin and respiratory system.
CHRONIC	Sand may become respirable size particles that contain crystalline silica. Long term inhalation of silica dust may cause silicosis and cancer.

3. INFORMATION ON INGREDIENTS

<u>COMPONENT</u>	<u>% BY WT</u>
Cement	15 - 35 %
Slag	min. 20% of OPC content
Sand	> 30 %
Filler	> 30 %
Additive	< 5 %
Polymer	> 7 %

SDS: DAVCO PANEL SKIMCOAT (INTERNAL)

4. FIRST AID MEASURES

(Applies to product as supplied and to the mixture with water)

INGESTION	Wash mouth and lips with water and seek medical attention.
EYE CONTACT	Immediately hold eyelids open and flush with plenty of water for 15 minutes, consult a doctor.
INHALATION	Move to fresh air and rest quietly. Consult a doctor if effect persists.

5. FIRE FIGHTING MEASURES

FLASH POINT	Non combustible
FLAMMABLE LIMIT LOWER UPPER	N. A. - -
EXTINGUISHING MEDIA	General extinguishing media. Foam, CO ₂ , Dry chemical, water fog.
SPECIAL FIRE FIGHTING PROCEDURE	None

6. ACCIDENTAL RELEASE MEASURES

Avoid skin or eye contact. Stop pedestrians from walking through the spill. Sweep up and collect any dry spilt product. Final clean-up should be with water. Do not allow material to enter drain or waterways. The unmixed products should be handled appropriately for disposal at approved landfill sites.

7. HANDLING AND STORAGE

PERSONAL PROTECTION	Precaution should be taken to avoid skin or eye contact or swallowing the product. When handling or mixing the dry product avoid inhaling dust. Wear dust mask, safety glasses, chemical resistant apron and impervious gloves; e.g. PVC. Always wash hand before eating, drinking or visiting the toilet.
FLAMMABILITY	This product is non-flammable.

SDS: DAVCO PANEL SKIMCOAT (INTERNAL)

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROL	N. A.
PERSONAL PROTECTION	Wear only a European Standard EN149 or N95 NIOSH certified respirator, safety glasses with side-shield (frame goggles) (EN166), chemical resistant apron and boots. Suitable safety gloves according to EN420 or suitable chemical resistance safety gloves according to EN374. Always wash hand before eating, drinking or visiting the toilet.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Fine Grey Powder
ODOUR	None
NON VOLATILE BY WT.	N. A.
pH	Alkaline (when mixed with water)
SOLUBILITY IN WATER	Insoluble
VISCOSITY	N. A.
FREEZING POINT	N. A.
BOILING POINT	N. A.
VAPOUR PRESSURE	N. A.
SPECIFIC GRAVITY	N. A.
VAPOUR DENSITY	N. A.

10. STABILITY AND REACTIVITY

STABILITY	Stable at normal temperatures when kept dry. When wet, sets to a hard lump with evolution of small amounts of heat.
MATERIALS AND CONDITIONS TO AVOID	Material is alkaline when mixed with water
HAZARDOUS DECOMPOSITION PRODUCTS	None known

SDS: DAVCO PANEL SKIMCOAT (INTERNAL)

11. TOXICOLOGICAL INFORMATION

INGESTION	No specific data available. Not regarded as harmful by ingestion. Unlikely to cause any serious ill effects. May cause minor upset or irritation to the digestive system.
INHALATION	Dust arising from the preparation is not likely to cause significant disease or toxic effect if exposure is kept under reasonable control.
SKIN CONTACT	Prolonged contact may cause irritation, especially if wet.
EYE CONTACT	Can cause serious damage to eyes

12. ECOLOGICAL INFORMATION

This material is not known as biodegradable.

13. DISPOSAL CONSIDERATIONS

This preparation is not classified as special waste under the Singapore control of pollution. Consult local regulations before disposal.

14. TRANSPORT INFORMATION

No special packaging requirements. Not classified as dangerous goods under the United Nations Transport Recommendations.

UN Number	N. A.
UN proper shipping name	N. A.
Transport hazard class (es)	N. A.
Packing group	N. A.
Marine pollutant	N. A.
Transport in bulk	N. A.
Special precaution	N. A.

SDS: DAVCO PANEL SKIMCOAT (INTERNAL)

15. REGULATORY INFORMATION

Not classified as dangerous under current regulation.

16. OTHER INFORMATION

The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. Any suggestion and recommendations made are without guarantee and liability since conditions of use are beyond our control. Appropriate warning and safe handling procedures should be provided to all those who handle and use the product and no liability can be accepted for any loss, injury or damage resulting from its use.

N. A. = Not Applicable

Date of Issue: Nov 2016 (Rev.01)