



# D PRIME

## WATER BASED ACRYLIC PRIMER

### DESCRIPTION

Davco D Prime is specially formulated for use as a primer, sealer and bonding agent. It can be used to prime floor and wall surfaces prior to the application of tile adhesive.

### USES

As primer on various surfaces such as plywood and drywall to enhanced adhesion strength & provide waterproofing prior to tiling works.

### SURFACE PREPARATION

General

Wallboards, flooring grade particle board and fibrous cement sheet must be firmly fixed in accordance with manufacturer's instructions.

Screw or nail heads must be sealed with epoxy resin. Gyprock joints need to be covered with 50mm wide gyprock tape.

All surfaces must be structurally sound, dry and free from dust, grease, wax, oil, curing compounds and other loose contaminating materials.

All loose mortar or plaster, etc must be removed and then the entire area cleaned to remove dust and dirt.

Ensure that surface is dry and clean and free from curing compound or release agents.

No chipping or roughening of surface is required if the condition is stable. Old paint work which are stable can remain.

Any contamination including commercial detergents used for cleaning must be thoroughly rinsed off with plenty of water.

### TECHNICAL DATA

#### Physical Properties

|                      |               |
|----------------------|---------------|
| Flash Point          | Non Flammable |
| Drying Time          | 60 min        |
| Water Resistance     | Very Good     |
| Adhesion to Concrete | > 0.8 MPa     |

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.





# D PRIME

## APPLICATION

Apply the area using either a roller or brush, with Davco D Prime, directly from the can. Do not dilute as product is supplied ready to use. Ventilate area with an industrial fan and allow 1 - 2 hours for the coat to dry before subsequent tiling works.

Do not apply if temperature is in excess of 45°C or less than 10°C.

## COVERAGE

1.5 - 2.0 m<sup>2</sup> per litre depending on the substrate condition.

## PACKAGING

Davco D Prime is available in 20 litres pail.

## SHELF LIFE

Shelf life of up to 12 months from the date of manufacture. Store in a cool place away from direct sunlight. Avoid freezing of the primer.

## CLEANING

Clean all brushes, rollers, trays, buckets and surrounding areas with clean water before the product sets.

## HEALTH & SAFETY

Davco D Prime is non toxic. In case of excessive skin contact, thoroughly flush with clean water. If ill effects occur, seek medical attention promptly. Refer to safety data sheet.

### Disclaimer

The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subjected to changes without prior notice. Before application, customers and users are requested to check that they have the latest version of this document from our website [www.parexgroup.com.sg](http://www.parexgroup.com.sg)



Certificate SG09/02195



Certificate SG95/06111



Certificate SG09/50075



ISO 14004 : 2006  
Certificate No. M-SYS / GHG / 8802



a member of

## PAREXGROUP PTE LTD

28 TUAS SOUTH AVENUE 8, SINGAPORE 637648

TEL: (65) 6861 0632 FAX: (65) 6862 3915

EMAIL: SALES@PAREXGROUP.COM.SG

WEBSITE: WWW.PAREXGROUP.COM.SG

ParexGroup, a French multi-national company with headquarters in Paris, is a leading manufacturer of speciality products for the construction industry with operations in more than 20 countries, and our 2700 people around the world are the cornerstone of our growing organization.

Updated WP58 Oct 2015