



MASONRY COARSE PLASTER ECO

**ENVIRONMENTALLY FRIENDLY,
COARSE MORTAR PLASTER**



ECO FRIENDLY



**LOW CARBON
FOOTPRINT**



EASE OF USE

DESCRIPTION

Davco Masonry Coarse Plaster ECO is an environmentally friendly, high quality premixed cementitious plaster comprising of Ordinary Portland Cement, approved recycled material, graded sand and chemical additives .

Davco Masonry Coarse Plaster ECO is an excellent plaster that provides superior bonding to concrete substrate, brickwork surfaces and is suitable for both internal and external plastering.

Davco Masonry Coarse Plaster ECO is approved by the Eco-labelling authority in Singapore as a sustainable building material.

USES

Davco Masonry Coarse Plaster ECO is an extremely versatile material highly recommended for bedding, pointing brickwork and blockwork, backing and bedding for wall tiles. It is also recommended for both internal and external plastering.

Davco Masonry Coarse Plaster ECO can be used for all types of concrete substrate, lightweight autoclaved aerated blocks, brickwall and blockwall.

ADVANTAGES

- Premixed to ensure good consistent quality.
- Prepacked for convenience in handling.
- Mixing and application made easy.
- High bonding strength.
- Good weather resistance and high durability.

TECHNICAL DATA

Appearance	: Grey
Tensile Adhesion Strength @ 14 days	: 1.8 N/mm ²
BS EN 1015 - 12 : 2000	
Water Retentivity	: ≥95%
BS 4551 : 2005 + A1 : 2010	
Linear Shrinkage	: 0.10%
Shear Adhesion Strength	: 1.2 N/mm ²
Stiffening Time	
BS EN 1015 - Part 9 : 1999	
@ 1.0 N/mm ²	: 5 hrs 4 mins
@ 2.0 N/mm ²	: 6 hrs 43 mins
Recommended Thickness	: 10mm to 15mm thick per layer of application
Consistency	: Homogeneous mortar paste
Binder	: Ordinary Portland Cement
Filler Material	: Precisely graded silica sand
Coverage	: 22 – 26m ² / mm / 40 kg bag
Maximum Aggregate Size	: < 5.5mm
Pot Life	: 60 minutes

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.



PAREX
Building expertise, together



MASONRY COARSE PLASTER ECO

SURFACE PREPARATION

Remove all dust, oil or traces of foreign materials. Dampen the dry concrete or plastered surface before application of Davco Masonry Coarse Plaster ECO .

MIXING

Add approximately 5.6 – 6.6 litres of water to 40 kg of Davco Masonry Coarse Plaster ECO. Mix thoroughly using an electrical mixer or a paddle mixer for 3 to 5 minutes until the desired homogeneous mortar paste is achieved. Ensure the mix is free from lumps before use.

APPLICATION

Davco Masonry Coarse Plaster ECO is applied using a steel trowel or spraying machine. It will remain workable for approximately 60 minutes after mixing.

Curing

In hot ambient temperature, the plaster should be cured with water spray during the first 2 days, for better shrinkage control.

PACKAGING

Davco Masonry Coarse Plaster ECO is supplied in 40 kg bag.

SHELF LIFE

Shelf life of up to 12 months from the date of manufacture, when stored in a dry place, free from moisture contact. Refer to safety data sheet.

HEALTH & SAFETY

Davco Masonry Coarse Plaster ECO is non-hazardous. In case of eye contact, wash with plenty of water. If irritation persists, seek immediate medical attention. Refer to safety data sheet.

Disclaimer

The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subjected to changes without prior notice. Before application, customers and users are requested to check that they have the latest version of this document from our website www.parexgroup.com.sg

PAREXGROUP PTE LTD

28 TUAS SOUTH AVENUE 8, SINGAPORE 637648

TEL: (65) 6861 0632 FAX: (65) 6862 3915

EMAIL: SALES@PAREXGROUP.COM.SG

WEBSITE: WWW.PAREXGROUP.COM.SG

ONLINE STORE: DAVCO-ONLINE.COM.SG

ParexGroup, a French multi-national company with headquarters in Paris, is a leading manufacturer of speciality products for the construction industry with operations in more than 20 countries, and our 2700 people around the world are the cornerstone of our growing organization.

Updated RD09 Jul 2018



Certificate SG09/02195



Certificate SG95/06111



Certificate SG09/50075



ISO 14064 : 2006
Certificate GMS-C / GHG / 0002

