



SK PRIMER

PENETRATING PRIMER

DESCRIPTION

Low viscosity latex-bitumen compound used as a penetrating primer.

USES

As a primer for improved adhesion of bitumen based preformed sheet membranes such as Davco SK2000S, Davco SK Fastorch, etc.

As a protective coating for concrete against biological growth or polluted soil.

ADVANTAGES

Very good adhesion coating to concrete, masonry, plaster, precast concrete and metal.

Resistant to deterioration.

Solidifies rapidly.

One component, easy to apply.

TECHNICAL DATA

Colour	Black
Specific Gravity	0.92
Drying Time	15 - 30 mins

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.





SK PRIMER

SURFACE PREPARATION

Surfaces must be sound, clean, dry, free from loose cement particles, grease, oil, curing compounds, or any other contaminants.

APPLICATION

Davco SK Primer to be applied directly from the can using a brush, roller or suitable spray equipment.

After approx. 1 - 3 hours (depending on climatic conditions) drying period, the membrane can be adhered.

COVERAGE

Approx. 6 - 8 m² per litre depending on the substrate condition.

PACKAGING

20 litres pail.

SHELF LIFE

Up to 12 months in unopened containers, when stored in a cool and dry place.

HEALTH AND SAFETY

- This product contains solvent.
- Do not inhale or swallow.
- Avoid contact with eyes and skin.
- Wear protective gloves and goggles.
- FLAMMABLE
- Refer to safety data sheet.

Disclaimer

The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subjected to changes without prior notice. Before application, customers and users are requested to check that they have the latest version of this document from our website www.parexgroup.com.sg



Certificate SG09/02195



Certificate SG95/06111



Certificate SG09/50075



ISO 14004 : 2006
Certificate No. M-SYS / GHG / 8802



PAREXGROUP PTE LTD

28 TUAS SOUTH AVENUE 8, SINGAPORE 637648

TEL: (65) 6861 0632 FAX: (65) 6862 3915

EMAIL: SALES@PAREXGROUP.COM.SG

WEBSITE: WWW.PAREXGROUP.COM.SG

ParexGroup, a French multi-national company with headquarters in Paris, is a leading manufacturer of speciality products for the construction industry with operations in more than 20 countries, and our 2700 people around the world are the cornerstone of our growing organization.

Updated WP45 Oct 2015